Prepared For shaun miskelly

Company urban living

Date 17 February 2014

eBrochure

Brochure Builder
by Applied Energy Products Ltd

Quality solutions for heating, air and water management

applied energy

Contents

Premier Ultra DC2 and DC3 low energy use, centrifugal extractor fans
LV100 SELV 4" (100mm) axial, single speed extractor fans.
GX6 EC2 and GXC6 EC2 low energy use, axial extractor fans
Slimline 650C - Chrome Ultra Slim Push Button Electric Shower
Slimline 650 - White Ultra Slim Push Button Electric Showers
Slimline 620 - White Ultra Slim Electric Showers
Powerstream - Unvented Instantaneous Water Heaters
Complete Care Pack CCP1
Extended Control Lever LEV2
New SL100 Range of 100mm Slimline Axial Fans with AC Motors
ACCPKD - Jessica 6 Mode Chrome Electric Shower Accessory Kit
ACCPKC - Isobella 3 Mode Chrome Electric Shower Accessory Kit
ACCPKB - Maria Single Mode Chrome Electric Shower Accessory Kit
ACCPKA - Viola 3 Mode White Electric Shower Accessory Kit
Redring Xpressions ECO-T range of Thermostatic Electric Showers
New Powerstream Eco Unvented Instantaneous Water Heater
New Active Range of Electric Showers
New Active Plus Range of Electric Showers
New Xpelair Contour Range of 100mm Discreet Extract Fans with AC motors
Redring Xpressions Range of Electric Showers
Redring Xpressions Plus Range of Electric Showers
Redring Xpressions Premier Range of Electric Showers

Approvals

Key Features

Extra long life Ultra DC motors
Now with integral power supply
Easy fit motor cassette
Filterless, easy maintenance
Meets Building Regulations for continuous and intermittent use
Intermittent operation selectable
Suitable for wall or ceiling mounting
Removable impeller for cleaning and ease of maintenance
Humidity control (CF model)
5 year motor guarantee
IPX5 suitable for wet zones 1 and 2

The Range

Premier Ultra DC2 fans are supplied with a separate remote mounted LV transformer, whilst the DC3 models have their own integral power supply built in the fan.

Both ranges feature long life, low energy use motors and are suitable for through the wall or ducted applications in bathrooms, toilets and other small wet rooms.

Finished in white, Premier Ultra DC extractor fans can be flush or surface mounted, with a 100mm circular spigot for rear entry or via the knock out connection for flat vertical ducting system.

A clip off front cover, pull off impeller and easy fit motor cassette feature simplifies maintenance and assists in quick and simple installation.

Ultra DC fans have a constant trickle feature, which means that when units are installed in every wet area of the property it can be classed as a whole house system, allowing it to comply with current building regulations for either intermittent or continuous extract.

The Premier has versatile standard built-in options, which allows the installer to select a combination of features: humidity control, adjustable overrun timer and Quick Visit delay start and pullcord boost override.

WD100 Wall Duct
89543AA

EFT Easy-fix Termination Kit
90427AA

Premier LVCF20T DC2 low energy use centrifugal extract fan
92335AW

Premier LVDX200T DC2 low energy use centrifugal extract fan
92439AW

Premier DX200T DC3 low energy use centrifugal extract fan
92575AW

Premier CF20T DC3 low energy use centrifugal condensation control fan
92576AW

LV100 SELV 4" (100mm) axial, single speed extractor fans.

Approvals

BEAB Approved

Key Features

Single speed SELV 100mm (4") axial extract fans with remote transformer
Six model range remotely switched, integral pullcord, timer, humidistat, PIR or control options
- Maximum fan performance 24 l/s
- Lubricated for life motors with thermal cut-out protection
- Clip-off front cover for ease of cleaning
- Fan units are IPX5 rated
- BEAB approved

The Range

LV100 fans are 12V Safety Extra Low Voltage (SELV) 100mm (4") axial extractor fans, offering complete peace of mind.

These fans are specifically designed to be installed directly over the splash area zone 1 in complete safety, with the SELV transformer sited out of reach of any person using the bath or shower.

All models come complete with a universal mounting kit and are suitable for wall, ceiling or window mounting (in single glazing up to 6mm) applications. The kit includes an air operated backdraught shutter and all models are supplied with a 12V SELV transformer.

Control options include integral pullcord and timer. Humidistat and PIR options offer automatic control. The LV100 range conforms to Building Regulations mechanical ventilation for toilets and bathrooms.

LV100 SELV 4" (100mm) axial, single speed extractor fans.: M

DXDG Glass Mounting Kit
07439AA

LVH LoVolt Remote Humidistat
21863AW

VC10 Vent Cowl
89531AA

XCT100 Condensation Trap
89749AA

XAA Airbrick Adaptor
89777AA

EFT Easy-fix Termination Kit
90427AA

LV100
90845AW

LV100PC
90846AW

LV100T
90847AW

LV100PIR
90867AW

LV100HTA
92569AW

LV100HTAP
92570AW

GX6 EC2 and GXC6 EC2 low energy use, axial extractor fans

Approvals

Key Features

Two model range

Installer select single speed 6" axial extract fans or two speed with COS (change over switch) accessory

Extract performance 40 l/s or 79 l/s

GX6 EC2 remotely switched with silent electro-thermal actuated shutter

GXC6 EC2 pullcord operated with mechanical louvered backdraft shutter

Energy saving long-life lubricated for life motors with thermal cut-out protection

Clip-off front cover and shutter cassette for ease of cleaning

BEAB approved

The Range

GX6 EC2 fans with Ultra EC motor technology are energy efficient long life 6" axial extractor fans. GX6 EC2 and GXC6 EC2 are designed with installer selectable settings to satisfy Part F1 installed performances for intermittent ventilation in kitchens or utility rooms.

GX6 has a silent backdraft shutter operation using an electro thermal actuator, whilst the GXC6 shutter is pullcord operated.

GX6 EC2 and GXC6 EC2 models feature a choice of installed performances and offer a longer life expectancy and lower energy use than a conventional AC motor.

WK6/8 GX6 Wall Kit
89369AA

WK6/11 GX6 Wall Kit
89370AA

PG6 (GX6, GXC6, WX6) Protective Wall Grille
89375AA

GXL20 (20 Pack) GX Longer Length Ladder Strips
89382AA

GX6 EC2
92294AW

GXC6 EC2
92295AW

Slimline 650C - Chrome Ultra Slim Push Button Electric Shower

Approvals

Key Features

Ultra slimline profile
Push button power selection and on/off
3 power settings
Rotary flow/temperature control for set and forget convenience
LED power installation
Multi-service points for ease of installation
All chrome accessory kit with a 6 spray mode rub-clean handset

The Range

The Slimline 650C electric shower has a contemporary chrome, ultra slimline profile, generating more space in a shower cubicle. It is fully temperature stabilised and has the added convenience of a push button on/off and power selection facility. The phased shutdown feature ensures that temperatures are managed to deliver a cool and safe start-up for the next user.

Slimline 650C - Chrome Ultra Slim Push Button Electric Shower

Slimline 650 Chrome 8.5kW
53557202

Slimline 650 Chrome 9.5kW
53558202

Slimline 650 - White Ultra Slim Push Button Electric Showers

Approvals

Key Features

Ultra slimline profile
- Push button power selection and on/off
- 3 power settings
- Rotary flow/temperature control for set and forget convenience
- LED power indication
- Multiple-service points for ease of installation
- White and chrome accessory kit with a 3 spray mode rub-clean handset

The Range

The Slimline 650 electric shower has an ultra slimline profile, generating more space in a shower cubicle. It is fully temperature stabilised and has the added convenience of a push button power selection facility. The phased shutdown feature ensures that temperatures are managed to deliver a cool and safe start-up for the next user.

Slimline 650 - White Ultra Slim Push Button Electric Showers: M

Slimline 650 8.5kW
53557201

Slimline 650 9.5kW
53558201

Slimline 650 10.5kW
53559201

Slimline 620 - White Ultra Slim Electric Showers

Approvals

Key Features

Ultra slimline profile
- Push button for on/off selection
- Rotary power select
- Rotary flow/temperature control
- 4 power settings
- Multi-service points for ease of installation
- All white accessory kit with a 3 spray mode rub-clean handset

The Range

Packed full of features, the Slimline 620 electric shower, with its ultra slimline profile, timed phased shutdown, overheat protection and multi-mode handset is an ideal choice for upgrading or replacing existing shower installations to generate more space in a shower cubicle.

Slimline 620 - White Ultra Slim Electric Showers: Models

Slimline 620 8.5kW
53555201

Slimline 620 9.5kW
53556201

Powerstream - Unvented Instantaneous Water Heaters

Approvals

Key Features

12kW unit is the highest rated single phase heater on the UK market

Water supplied to either one or two outlets: Either two hand wash basins (Please note when both are in use the hot water flow will be shared between the two outlets) Or one hand basin and a shower using the dedicated Redring Powerstream Mixer Accessory Kit (Please note only one outlet may be used at any one time)

Water outlet via the Redring1/4 turn spray tap

Direct mains supply

Small compact shape

Remote fitting option

No standing heat losses

Fast response

Half power selection available on installation

Corrosion resistant steel backplate

The Range

The Redring Powerstream unvented instantaneous water heater delivers instant hot water at point of use. This compact and unique design eliminates the need for centrally stored hot water cylinders saving on electricity usage and important space.

Powerstream - Unvented Instantaneous Water Heaters: Models

Powerstream 9.5
45793201

Powerstream 12
45793202

Powerstream 10.8
45793204

Lever Control Spray Tap (Pair) LT1
85793616

Shower Mixer Kit RM1
85793620

Complete Care Pack CCP1

Approvals

Complete Care Pack CCP1: Models

Electric Shower Accessories

7066

Extended Control Lever LEV2

Approvals

Extended Control Lever LEV2: Models

Electric Shower Accessories

7066

New SL100 Range of 100mm Slimline Axial Fans with AC Moto

Approvals

Key Features

A range of five compact, low profile single speed 100mm (4") axial extract fans
Models include remotely switched (SL100), integral pullcord (SL100P), timer (SL100T), humidistat with timer control options (SL100HT) and PIR control (SL100PIR)
Unobtrusive low profile fan with sleek styling
Pack comes complete with an integral backdraft shutter
Suitable for use in temperatures up to 50°C
Can be wall or ceiling mounted for ease of installation
IPX4 rated for peace of mind
Made in the UK

The Range

Xpelair's brand new generation of 100mm Slimline fans are one of the lowest profile fans on the market, offering both performance and style as standard. With an external projection of only 14mm and a stylish white finish the range will meet any design criteria.

Easy to install and maintain, Xpelair's new SL100 range is perfect for refurbishments and minor works in bathrooms and toilet applications. This easy to use single speed unit comes complete with a range of control options that will fit all build applications. Humidistat models adjustable from 65-85% RH, timer options adjustable up to 30 minutes and PIR sensors for less populated areas are available.

With the units designed specifically for small bathrooms and toilets they come complete with internal backdraft shutters and extract directly to outside atmosphere or alternatvely through a short duct run.

New SL100 Range of 100mm Slimline Axial Fans with AC Moto

Xpelair SL100
92674AW

Xpelair SL100P
92675AW

Xpelair SL100T
92676AW

Xpelair SL100HT
92677AW

Xpelair SL100PIR
92678AW

ACCPKD - Jessica 6 Mode Chrome Electric Shower Accessory

Approvals

ACCPKD - Jessica 6 Mode Chrome Electric Shower Accessory

Redring Expressions 550S 8.5kW Shower (2006 - Current)
53674001_spares

Redring Expressions 550S 9.5kW Shower (2006 - Current)
53674501_spares

ACCPKC - Isobella 3 Mode Chrome Electric Shower Accessory

Approvals

ACCPKC - Isobella 3 Mode Chrome Electric Shower Accessory

Redring Expressions 500S 7.2kW Shower (2006 - Current)
53672501_spares

Redring Expressions 500S 8.5kW Shower (2006 - Current)
53673001_spares

Redring Expressions 500S 9.5kW Shower (2006 - Current)
53673501_spares

ACCPKB - Maria Single Mode Chrome Electric Shower Accesso

Approvals

MCDPKB - Maria Single Mode Chrome Electric Shower Acc

Redring Active 350S 7.2kW Shower (1996 - Current)
53671501_spares

Redring Active 350S 8.5kW Shower (2006 - Current)
53672001_spares

ACCPKA - Viola 3 Mode White Electric Shower Accessory Kit

Approvals

ACCPKA - Viola 3 Mode White Electric Shower Accessory Kit: M

Redring Active 320S 7.2kW Shower (2006 - Current)
53670501_spares

Redring Active 320S 8.5kW Shower (2006 - Current)
53671001_spares

Redring Xpressions ECO-T range of Thermostatic Electric Show

Approvals

Key Features

Thermostatic control to ensure minimal hassle and maximum showering efficiency while maintaining shower temperature to between +/- 1.5°c
The in built temperature limiter is factory set at 46?C but is adjustable to 43?C for complete safety
Eco Power button to ensure complete energy efficiency and reduced running costs
Unique Timer shower function, to promote sustainable usage and complete control
Push stop and start button with 'Set and forget' feature for ease of control
Three kW options available - 7.2kW, 8.5kW and 9.5kW
Phased shut down feature for complete peace of mind
BEAB Approved
IPX4 rated for increased safety
Blue LED illumination power select indicator giving direct user feedback
6 different spray patterns
Dimensions: Height 364mm and width 264mm

The Range

Redring are pleased to introduce the brand new Xpressions ECO-T range. As part of Redring's Intelligent showering offer, the Xpressions ECO-T is the ideal showering experience for the whole family. The state of the art electronically controlled thermostatic shower comes complete with new patented* control technology, to ensure ease of use and environmental sustainability.

The unique shower selection features include High, Eco and Timer settings for complete control. With increased focus towards 'social responsibility' and water efficiency Redring have manufactured one of the most sustainable, intelligent showering solutions on the market.

With easy to use push button start and rotary temperature selection, LED indicator for user feedback and patented* thermostatic control feature. The brand new Xpressions ECO - T is the most advanced family shower available; the thermostatic control allows the flow of constantly regulated water temperature to be maintained to within +/- 1.5°C ensuring a safer hassle free showering experience for all.

For unique applications Redring will also be promoting three further contemporary product finishes in a 8.5kW ratings. Gloss piano black, matt silver and atlas chrome. These limited edition models will help create ambience in any bathroom application.

*patent pending at time of insertion

NEW Xpressions ECO-T 7.2kW White
53677701
New Xpressions ECO-T 7.2kW in White high gloss finish

New Xpressions ECO-T 8.5kW White
53678701

New Xpressions ECO-T 8.5kW Black
53678702

New Xpressions ECO-T 8.5kW Silver
53678703

New Xpressions ECO-T 8.5kW Chrome
53678704

New Xpressions ECO-T 9.5kW White
53679701

New Powerstream Eco Unvented Instantaneous Water Heater

Approvals

Key Features
Available in 9.5kW and 10.8kW models
Integral power level selections
Four power options – High, ECO, Low and Cold
Eco function allowing reduced running costs and minimising electrical wastage
Ease of control with the new adjustable power dial
Delivers hot water instantaneously at point of use eliminating the need to connect to a centrally located hot water cylinder with long pipe runs
Provides instant mains pressure hot water to one or two hand basin outlets
Suitable for dual basin or one basin with mixer shower kit*
Redring basin spray taps are recommended when two basins are fed from the same heater unit
Compact size
Option of multi directional mounting - see additional images for more information

*Dependant on flow rate

The Range
The new Powerstream ECO delivers hot water instantaneously at point of use eliminating the need to connect to a centrally located hot water cylinder with long pipe runs. This compact and unique design now offers an external power selection dial with an ECO setting for ease of use and reduced running costs.

With two kW variants 9.5 and 10.8, this direct fed water mains unit is ideal for hand basin supply in commercial washrooms and residential applications where access to stored hot water is limited.

The new Powerstream ECO benefits from user power level selections, enabling energy management and allowing the user to move between four power options – High, ECO, Low and Cold.

When running the Powerstream in the ECO setting, the power used to run the unit is reduced, minimising electrical wastage and running costs making it the ideal washroom solution.

View the new Redring Powerstream Eco Brochure PDF here

New Powerstream Eco Unvented Instantaneous Water Heater:

Redring Powerstream Eco 9.5kW
45673201

Redring Powerstream Eco 10.8kW
45673202

Lever Control Spray Tap (Pair) LT1
85793616

Shower Mixer Kit RM1
85793620

New Active Range of Electric Showers

Approvals

Key Features

Available in 7.2kW and 8.5kW
Three power settings for energy efficiency and reduced running costs
Ergonomic rotary control - upper dial for start/stop and power selection and lower dial for temperature/flow adjustment for simple operation
Right hand side, multiple connection options (top, bottom or rear cable access and top, bottom, rear or side pipe access)
Multiple fixing centres for ease of replacement of previous Redring Active models
Removable corner section for ease of installation
Gloss white finish and new contoured body styling to suit any bathroom decor
Accessory kit with 1 metre hose, soap dish and single mode rub-clean shower head
Dimensions: H: 330mm, W: 219mm, D: 95mm

The Range

The new Active range of instant electric showers is the latest addition to Redring's shower offering. With a new stylish appearance, the new Active range is the ideal solution for any domestic showering application.

The new Redring Active models offer a quick and easy installation. The multiple connection options (right hand top, bottom or rear cable access and right hand top, bottom, rear or side pipe access) enable the units to comfortably replace many market equivalents with ease. The backplates also feature multiple fixing centres which are identical to those used on previous Redring Actives, allowing the new units to directly replace existing Active models.

View the new Redring Active Range Brochure PDF here

New Active Range of Electric Showers: Models

Active 7.2kW electric shower
53561001

Active 8.5kW electric shower
53561201

New Active Plus Range of Electric Showers

Approvals

Key Features

Available in 7.2kW and 8.5kW
Push button start/stop for ‘set and forget’ seasonal operation
Three power settings for energy efficiency and reduced running costs
Ergonomic rotary control - upper dial for power selection and lower dial for temperature/flow adjustment for simple operation
Neon `power on’ and `auto reset’ indicators for improved user interaction
Right hand side, multiple connection options (top, bottom or rear cable access and top, bottom,rear or side pipe access)
Multiple fixing centres for ease of replacement of previous Redring Active models
Removable corner section for ease of installation
Gloss white finish and new contoured body styling to suit any bathroom decor
Accessory kit with 1.25 metre hose, soap dish and multi mode rub-clean shower head
Dimensions: H: 330mm, W: 219mm, D: 95mm

The Range

The new Active range of instant electric showers is the latest addition to Redring’s shower offering. With a new stylish appearance and the added feature of a push button start/stop control on the Plus models, the new Active range is the ideal solution for any domestic showering application.

The new Redring Active models offer a quick and easy installation. The multiple connection options (right hand top, bottom or rear cable access and right hand top, bottom, rear or side pipe access) enable the units to comfortably replace many market equivalents with ease. The backplates also feature multiple fixing centres which are identical to those used on previous Redring Actives, allowing the new units to directly replace existing Active models.

View the new Redring Active Range Brochure PDF here

New Active Plus Range of Electric Showers: Models

Active Plus 7.2kW electric shower
53561601

Active Plus 8.5kW electric shower
53561801

New Xpelair Contour Range of 100mm Discreet Extract Fans

Approvals

Key Features
AC motors
Single speed range
Discreet and stylish design
Features integral backdraught shutter
3 variants available: Integral pullcord (C100P), timer (C100T) and humidistat with timer (C100HT)
IPX 4 rated

The Range
The Xpelair Contour range is a discreet and stylish solution designed to provide effective ventilation wthout being overly conspicious. Its sleek, contoured fascia expertly blends into home décor, while its 48mm external projection makes it one of the lowest profile fans on the market.

Ideal for domestic bathrooms, shower rooms and toilets. The range conforms to the latest Building Regulations which makes it ideal for both new build and refurbishment applications. Suitable for wall or ceiling mounting, the fans feature easy fix 'quick clamps' to provide a strightforward installation.

Also available in a three speed energy efficient DC motor range. View the range here

View the PDF datasheet here

WT10 Termination Ducting Kit
89538AA

Flexible Ducting Xflex FD100 3m
89663AA

Flexible Ducting Xflex FD100 6m
89669AA

XCT100 Condensation Trap
89749AA

SL100 Slimline Wall Kit SLWK
91232AW

Xpelair C100P
92855AW

Xpelair C100T
92856AW

Xpelair C100HT
92857AW

Redring Xpressions Range of Electric Showers

Approvals

Key Features

Available in 7.2, 8.5 and 9.5kW options
'Smart fit' - maximum entry options for power/water services (top, rear or bottom) both left and right hand sides
Dual terminal blocks for left or right hand connection
Push button start/stop for simple 'set and forget' control
Upper rotary control with three power selection settings for energy efficiency and reduced running costs
Lower rotary control for adjustment of temperature/flow
'Power On' and 'Auto Reset' neon indicators
Removable water inlet filter
'Smart fit' accessory kit with sliding bracket fixing and three mode rub-clean shower spray head

The Range

The Xpressions range of electric showers is the first from Redring to feature both left and right hand installation entry points. The models feature 6 cable and 8 pipe entry points as well as dual terminal blocks for left or right connection to provide a simple and convenient electrical connection.

The Xpressions showers feature an easy to use push button start/stop for ‘set and forget’ seasonal operation and ergonomic rotary controls for power and temperature/flow.

The Xpressions also comes with Flexi Kit accessories, which features an adjustable top bracket to easily replace existing accessories with minimal disruption to bathroom décor.

View the new Xpressions range datasheet PDF here

Redring Xpressions Range of Electric Showers: Models

Redring Xpressions 7.2kW electric shower
53563001

Redring Xpressions 8.5kW electric shower
53563201

Redring Xpressions 9.5kW electric shower
53563401

Redring Xpressions Plus Range of Electric Showers

Approvals

Key Features

Available in 7.2, 8.5 and 9.5kW options
'Smart fit' - maximum entry options for power/water services (top, rear or bottom) both left and right hand sides
Dual terminal blocks for left or right hand connection
Push button start/stop for simple 'set and forget' control
Upper rotary control with three power selection settings for energy efficiency and reduced running costs
Lower rotary control for adjustment of temperature/flow
'Power On' and 'Auto Reset' neon indicators
Removable water inlet filter
'Smart fit' accessory kit with sliding bracket fixing and three mode rub-clean shower spray head
Scale flush protection/safety phased shutdown feature

The Range

The Xpressions range of electric showers is the first from Redring to feature both left and right hand installation entry points. The models feature 6 cable and 8 pipe entry points as well as dual terminal blocks for left or right hand connection to provide a simple and convenient electrical connection.

The Xpressions Plus showers feature an easy to use push button start/stop for ‘set and forget’ seasonal operation and ergonomic rotary controls for power and temperature/flow. They also feature Scale Flush technology to minimise lime scale build up and ensure a safe starting temperature for users.

The Xpressions Plus comes with Flexi Kit accessories, which feature an adjustable top bracket to easily replace existing accessories with minimal disruption to bathroom décor.

View the new Xpressions range datasheet PDF here

Redring Xpressions Plus Range of Electric Showers: Models

Redring Xpressions Plus 7.2kW electric shower
53565001

Redring Xpressions Plus 8.5kW electric shower
53565201

Redring Xpressions Plus 9.5kW electric shower
53565401

Redring Xpressions Premier Range of Electric Showers

Approvals

Key Features

Available in 8.5 and 9.5kW options
'Smart fit' - maximum entry options for power/water services (top, rear or bottom) both left and right hand sides
Dual terminal blocks for left or right hand connection
Push button start/stop for simple 'set and forget' control
Push buttons with neon indication for High or Medium power setting selection
Rotary control for adjustment of temperature/flow
Removable water inlet filter
'Smart fit' accessory kit with sliding bracket fixing and three mode rub-clean shower spray head
Scale flush protection/safety phased shutdown feature
Water saving 'Eco Timer' six minute shower function with neon indication

The Range

The Xpressions range of electric showers is the first from Redring to feature both left and right hand installation entry points. The models feature 6 cable and 8 pipe entry points as well as dual terminal blocks for both left or right hand connection, for a simple and convenient electrical connection.

The Xpressions Premier showers feature easy to use push button start/stop for ‘set and forget’ seasonal operation and push button power select, as well as ergonomic rotary controls for temperature/flow. The Xpressions Premier also features a unique 6 minute eco timer which allows the shower to be set to automatically switch off after a period of 6 minutes, saving water and energy. They also feature Scale Flush technology to minimise lime scale build up and ensure a safe starting temperature for users.

The Xpressions Premier comes with Flexi Kit accessories, which feature an adjustable top bracket to easily replace existing accessories with minimal disruption to bathroom décor.

View the new Xpressions range datasheet PDF here

Redring Xpressions Premier Range of Electric Showers: Models

Redring Xpressions Premier 8.5kW electric shower
53564001

Redring Xpressions Premier 9.5kW electric shower
53564201

Terms and Conditions

Disclaimer

Please be advised that technical specifications and other product information set forth in this document are provided for information only and are subject to change by the Company at any time without notice.

This document may contain inaccuracies and typographical errors. The Company does not warrant the accuracy or completeness of the materials or the reliability of any advice, opinion, statement or other information displayed or distributed through the document. Any reliance on such advice, opinion, statement or other information shall be at your own risk.

The information and materials in the document are provided "as is" without representation or warranty of any kind to the fullest extent permissible pursuant to applicable law, including but not limited to implied warranties of non-infringement, merchantability, satisfactory quality or fitness for a particular purpose.
Furthermore the Company accepts no responsibility or liability for, and makes no warranties that, functions contained at this site will not be interrupted or error-free or that defects will be corrected.
Please note that some jurisdictions do not allow the exclusions of implied warranties, so some or all of the above exclusions may not apply to you.

Limitation of Damages

In no event will the Company or any of its subsidiaries or its or their parent companies be liable to you for any direct, special, indirect, consequential, incidental damages or any damages of any kind even if the Company has been advised of the possibility thereof.

Applicable law may not allow the limitation or exclusion of liability for consequential or incidental damages, so the limitation or exclusion may not apply to you.

Choice of Law

The terms and conditions are governed by and shall be construed in accordance with the laws of England and Wales.

Illegality of terms

If any of these terms and conditions should be determined to be illegal, invalid or otherwise unenforceable by reason of the laws of any state or country in which these terms and conditions are intended to be effective, then to the extent and within the jurisdiction which that term or condition is illegal, invalid or unenforceable, it shall be severed and deleted from that clause and the remaining terms and conditions shall survive, remain in full force and effect and continue to be binding and enforceable.

Changes

Applied Energy Products Limited reserves the right, at its sole discretion, to change, modify, add or remove any portion of these terms and conditions in whole or in part, at any time. Changes to these terms and conditions will be effective when notice of such change is included in this document.

Copyright and Limited Licence

© Copyright Applied Energy Products Limited. All rights reserved.

This document and all content included in it (such as graphics, logos, icons, text and images) is copyrighted and protected by worldwide copyright laws and treaty provisions. You agree to comply with all copyright laws worldwide in your use of this document.

Subject to these General Terms and Conditions of use of this Document the Company grants you a non-exclusive, non-transferable, limited right to access, use and display this document and the materials thereon for your personal use.

All proprietary rights remain the property of the Company or, where used by the Company under licence, third party copyright owners.

Sales Team
tel 0844 372 7750
fax 0844 372 7760

Technical Advice
tel 0844 372 7766
fax 0844 372 7767

applied energy

Applied Energy Products Limited,
Morley Way,
Peterborough
PE2 9JJ
www.applied-energy.com

Document produced at 12:23pm 17/02/2014